

SAFETY DATA SHEET

Titanium Ti6Al4V

SECTION 1: Identification of the substance/mixture and of the company/undertaking

```
1.1. Product identifier
  Trade name
     Titanium Ti6Al4V
  Other names / Synonyms
     Document No. : H-5800-6819-01-A EN
  Product no.
     A-5771-0406
1.2. Relevant identified uses of the substance or mixture and uses advised against
  Relevant identified uses of the substance or mixture
     Metal powder for additive layer manufacture
  Uses advised against
     None known.
1.3. Details of the supplier of the safety data sheet
  Company and address
     Renishaw plc
     New Mills
     Wotton-under-Edge,
     GL12 8JR, Gloucestershire,
     United Kingdom
     +44 (0) 1453 524524
     www.renishaw.com
  E-mail
     msds@renishaw.com
  Revision
     09/02/2023
  SDS Version
     1.0
1.4. Emergency telephone number
  Contact The National Poisons Information Service (dial 111, 24 h service).
  See section 4 "First aid measures".
  Emergency contact from supplier: +44 (0) 1453 524524 (UK office hours 08:00 to 17:00 UTC Monday to Thursday, 08:00
  to 16:00 Friday)
SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
  Flam. Sol. 1; H228, Flammable solid.
2.2. Label elements
  Hazard pictogram(s)
```

Signal word Danger Hazard statement(s) Flammable solid. (H228) Safety statement(s) General -Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210) Response

In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378) Storage

Disposal

-

Hazardous substances

Aluminium

Additional labelling

Not applicable.

2.3. Other hazards

Additional warnings

Dust from flammable solids can be explosive, even if they are not hazardous substances.

May form combustible dust concentrations in air.

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Titanium	CAS No.: 7440-32-6 EC No.: 231-142-3 UK-REACH: Index No.:	80-90%		
Aluminium	CAS No.: 7429-90-5 EC No.: 231-072-3 UK-REACH: Index No.:	6-6.5%	Flam. Sol. 1, H228 Water-react. 2, H261	
Vanadium	CAS No.: 7440-62-2 EC No.: 231-171-1 UK-REACH: Index No.:	3.8-4.5%		

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-

30 °C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

None known.

4.3. Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Dry powder (Class D), sodium chloride (granulate) or dry sand. Unsuitable extinguishing media: DO NOT USE WATER!

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice. Hazchem Code: 4Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

Evacuate surrounding areas.

Eliminate all ignition sources.

Ventilate the area.

Wear appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Cleaning up the material must be done only with squeegees or soft natural bristle brushes. Scoops used to pick up the material must be conductive and non-sparking. Synthetic bristle brushes and plastic or other non-conductive scoops must not be used, since they tend to accumulate strong static charges.

Collect spills carefully. Moist the material with water in order to prevent the formation and propagation of dust.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

Use spark-proof tools and explosion-proof equipment.

Avoid dust generation.

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste. See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep all containers sealed except when opened for removal of material. Reseal containers immediately after each use



to prevent contamination or, in the case of pastes, loss of solvent.

Take precautionary measures against static discharges.

Smoking, drinking and consumption of food is not allowed in the work area.

Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers.

Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

See section 8 "Exposure controls/personal protection" for protective measures.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Keep all containers sealed except when opened for removal of material. Reseal containers immediately after each use to prevent contamination or, in the case of pastes, loss of solvent.

The use of an inert gas to replace air can greatly increase the safety of many operations, particularly where it may be impossible to ensure that all sources of ignition are eliminated.

Powder trickling out onto the floor or onto other containers must be prevented.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Avoid the suspension of dust in the air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use non-sparking tools.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Store in tightly closed original container in a dry, cool and well-ventilated place.

Store in accordance with local regulations.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Aluminium

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

No data available.

PNEC

No data available.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis. Where necessary use lighting and electrical equipment designed for use in atmospheres where flammable vapours or dusts are present, and which can direct static electricity by grounding equipment.

General recommendations

When transferring the materials, dust clouds should be kept at an absolute minimum. Handling should be slow and deliberate. The materials should be transferred from one container to another using a non-sparking, conductive metal scoop.

When mixing the material with other dry ingredients, frictional heat should be avoided. The best type of mixer for a dry mixing operation is one that contains no moving parts, but rather affects a tumbling action, such as a conical blender. Introduction of an inert atmosphere in the blender is highly recommended since dust clouds are generated. All equipment must be well grounded.

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

All electrical wiring, -lights and -equipment must meet minimum safety requirements of the workplace and equipment used in explosive atmosphere as described by national regulations and/or standards.



Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

8.3. Individual protection measures, such as personal protective equipment

Generally

Work clothing should be made of smooth, closely woven fire resistant/fire retardant fabrics which tend not to accumulate static electric charges. Trousers should have no cuffs where the material might accumulate. Pockets, if present, should be designed in such a way as to eliminate the accumulation of dust. Use only UKCA marked protective equipment.

Respiratory Equipment

copilatory Equ	ipinene			
Туре	Class	Colour	Standards	
SL	P3	White	EN149	R

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	R
Safety shoes		EN ISO 20345	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	0,3	> 480	EN374-2, EN374-3, EN388	

Eye protection

Туре	Standards
Safety glasses with side shields.	EN166

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Powder Colour Gray Odour / Odour threshold None pH Not applicable - product is a solid Density (g/cm³) ≈ 4.43 Relative density No information available as testing has not been completed. Kinematic viscosity

Not applicable - product is a solid Particle characteristics Particle size: 15-45 um Size distribution: Ti-6Al-4V 15-45 microns: (D10 - 21 um / D50 - 32 um / D90 - 49 um). Phase changes Melting point/Freezing point (°C) 1605 - 1660 Softening point/range (waxes and pastes) (°C) Does not apply to solids. Boiling point (°C) No information available as testing has not been completed. Vapour pressure Testing not relevant or not possible due to the nature of the product. Relative vapour density Does not apply to solids. Decomposition temperature (°C) No information available as testing has not been completed. Data on fire and explosion hazards Flash point (°C) Not applicable - product is a solid Ignition (°C) ≈ 493 Auto flammability (°C) ≈ 325 Lower and upper explosion limit (% v/v) No information available as testing has not been completed. Solubility Solubility in water Insoluble n-octanol/water coefficient No information available as testing has not been completed. Solubility in fat (g/L) No information available as testing has not been completed. 9.2. Other information Formation of explosible dust/air mixtures Yes Dust explosion class St1 (Weak explosion) Dust deflagration index (Kst) (bar.m/s) 60 Evaporation rate (n-butylacetate = 100) Not applicable - product is a solid Other physical and chemical parameters No data available. SECTION 10: Stability and reactivity 10.1. Reactivity No data available. 10.2. Chemical stability The product is stable under the conditions, noted in section 7 "Handling and storage". 10.3. Possibility of hazardous reactions None known. 10.4. Conditions to avoid Avoid static electricity.

Avoid the suspension of dust in the air.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Product/substance	Titanium
Test method:	OECD 425
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/kg bw/day
Other information:	

Product/substance	Vanadium
Test method:	OECD 423
Species:	Rat
Route of exposure:	Oral
Test: Result: Other information:	LD50 >2000 mg/kg bw/day

Product/substance	Vanadium
Test method:	OECD 436
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	>5.05 mg/L
Other information:	

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met. Skin sensitisation

Based on available data, the classification criteria are not met. Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met. STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met. Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

None known.

Other information

None known.

Exposure to metal dusts and oxides may cause metal fume fever. Metal fume fever is a temporary flu-like condition characterized by chills, fever, muscle aches and pains, nausea, and vomiting. Typically, the symptoms appear within a few hours after exposure and subside within 2-3 days with no permanent effects.

SECTION 12: Ecological information

12.1. Toxicity



	nume				
14.1 UN / ID		14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ION 14: Trans	port information				
		product must be di	sposed of simi	larly to the product.	
t applicable.	ing				
t applicable. ic labelling					
gulation (EU) N ode		ecember 2014 on w	aste as retaine	ed and amended in Ul	K law.
duct is covere	ed by the regulations	on hazardous wast	e.		
treatment m	ethods				
ION 13: Dispo	osal considerations				
Other adverse ne known.	e effects				
ne known.					
′B.		i any substances co	onsidered to m	eet the criteria classif	ying them as PBT and/
Results of PBT	and vPvB assessmen				
Mobility in soi	1				
Bioaccumulati	ive potential				
Persistence ar	nd degradability				
ult:	2907 µg/L				
ation:	72 hours				
t method: cies:	OECD 201	lesmus subspicatus			
ult:	693 µg/L				
ation:	96 hours				
cies:		idus			
ation: t:	72 hours EC50				
cies: npartment:	· · · · · · · · · · · · · · · · · · ·				
	appartment: ation: ation: ation: ation: ation: creation duct/substance timethod: creation: ation: ation: ation: ation: ation: creation: ation: ation: creation: ation: ation: creation: ation: ation: ation: ation: ation: ation: creation: ation: ation: ation: ation: ation: creation: ation: ation: ation: creation: ation	ation: 72 hours ation: 72 hours ation: 72 hours c: EC50 ult: >10000 mg/L er information: Fish, Leuciscus duct/substance Vanadium cies: Fish, Leuciscus ation: 96 hours cies: LC50 ult: 693 µg/L er information: OECD 201 cies: Algae, Desmoor npartment: ation: ation: 72 hours : ErC50 ult: 2907 µg/L er information: Persistence and degradability data available. Bioaccumulative potential data available. Bioaccumulative potential data available. Results of PBT and vPvB assessmen s mixture/product does not contain Bioaccumulative potential data available. CON 13: Disposal considerations treatment methods Guct is covered by the regulations of a splicable. ic labelling applicable. ic labelling applicable. ic labelling applicabl	npartment: 72 hours time to 2 hours time to 2 hours time thod: 2000 mg/L er information: duct/substance Vanadium rmethod: 0ECD 203 cies: Fish, Leuciscus idus npartment: 4 dion: 96 hours time LC50 ult: 693 µg/L er information: duct/substance Vanadium time thod: 0ECD 201 cies: Algae, Desmodesmus subspicatus npartment: 4 duct/substance Vanadium time thod: 0ECD 201 cies: Algae, Desmodesmus subspicatus npartment: 20 hours time trobd: 2007 µg/L er information: Persistence and degradability data available. Results of PBT and vPvB assessment s mixture/product does not contain any substances cors andocrine disrupting properties ne known. Other adverse effects he known. Other adverse effects he known. Other adverse effects he known. CON 13: Disposal considerations treatment methods duct is covered by the regulations on hazardous wasta 3 - Flammable ulation (EU) No 1357/2014 of 18 December 2014 on woode applicable. is clabelling applicable. is clabelling applicable. minated packing kaging containing residues of the product must be di CON 14: Transport information 14.1 14.2 UN / ID UN proper shipping Hazard class(es)	npartment: ation: 72 hours ECS0 Jult: > >10000 mg/L er information: duct/substance Vanadium imethod: OECD 203 cies: Fish, Leuciscus idus npartment: ation: 96 hours E. LCS0 Jult: 693 µg/L er information: duct/substance Vanadium imethod: OECD 201 cies: Algae, Desmodesmus subspicatus npartment: ation: 72 hours E. ErC50 Jult: 2907 µg/L er information: Persistence and degradability data available. Nobility in soil data available. Addata available. Addata available. Sioaccumulative potential data available. Addata available. Sioaccumulative potential data available. Addata available. Mobility in soil data available. Sioaccumulative potential data available. Sioaccumulative potential data available. Mobility in soil data available. Sioaccumulative solutions on hazardous waste. 3 - Flammable julation (EU) No 1357/2014 of 18 December 2014 on waste as retained ode a applicable. ic clabelling applicable. ic applicable. ic applicab	npartment: Z hours EC50

Classification code:

F3

(Aluminium)

Tunnel restriction

code: (E)



	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
						See below for additional information.
IMDG	UN3089	METAL POWDER, FLAMMABLE, N.O.S. (Aluminium)	Class: 4.1 Labels: 4.1 Classification code: F3	Π	No	Limited quantities: 1 kg EmS: F-G S-G See below for additional information.
ΙΑΤΑ	UN3089	METAL POWDER, FLAMMABLE, N.O.S. (Aluminium)	Class: 4.1 Labels: 4.1 Classification code: F3	Π	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods. Hazchem Code: 4Y

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

Regulation on explosives precursors Aluminium (Annex II)

Additional information

Not applicable.

Sources

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law. Council Regulation (EC) No 2019/1148 on explosives precursors as retained and amended in UK law. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law. Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment



No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3 H228, Flammable solid. H261, In contact with water releases flammable gases. Abbreviations and acronyms ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CE = Conformité Européenne CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario EUH statement = CLP-specific Hazard statement EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer (IARC) IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SCL = A specific concentration limit SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVBC = Unknown or variable composition, complex reaction products or of biological materials VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Additional information The classification of the mixture in regard to physical hazards has been based on experimental data. The safety data sheet is validated by EcoOnline Other A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle. The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en